

Fixed Attenuator

DC to 18 GHz
6 dB
5 Watt
SMA Stainless Steel Connectors


Features

- High attenuation accuracy
- Small VSWR
- Stainless Steel
- Ceramic chip
- Low cost-high performance

Specifications

Frequency Range	DC to 18 GHz
Attenuation	6 dB
Attenuation Accuracy (Max.)	± 0.5 dB over DC - 18 GHz
Nominal Impedance	50 Ohm
Average Power	5 Watt
Operating Temperature	-55 to +150

Model No. Description

FATXXXXXX
X- power handling: 2W or 5W.

X- connector type: SMA, N type or SMB connector.

XX- attenuation: **dB.

XX- frequency range, 06: DC to 6GHz

14: DC to 14GHz

18: DC to 18GHz.


FREQ. RANGE (GHz)	Typical VSWR(:1)	Maximum VSWR(:1)
DC to 6	1.20	
6 to 12	1.25	
12 to 18	1.35	
DC to 18		1.40

Material & Plating


Parts	Material	Plating(Micro-inch)
Body & Nut	Stainless Steel	Passivated
Contact (female & male)	Beryllium Copper	Gold 30
Insulator	Teflon	

Characteristic

For example the testing curves of FAT1806S5



Package Outlines



Package type: SMA

Note: all dimensions shown in mm & inch

Yantel Corporation

Add : 3F, Building 3, Southern District 2 of Zhongguan Honghualing Industrial Park, Xili, Nanshan, Shenzhen, China

Tel : 86-755-8355-1886 Fax : 86-755-8355-2533

 For detailed performance specs & shopping online see Yantel web site : www.yantel-corp.com