

Fixed Attenuator

DC to 18 GHz
10 dB
2 Watt
SMA Stainless Steel Connectors



Features

- High attenuation accuracy
- Small VSWR
- Stainless Steel
- Ceramic chip
- Low cost-high performance

Specifications

Frequency Range	DC to 18 GHz
Attenuation	10 dB
Attenuation Accuracy (Max.)	± 1.0 dB over DC - 18 GHz
Nominal Impedance	50 Ohm
Average Power	2 Watt
Operating Temperature	-55 to +150

Model No. Description

FATXXXXXX

X- power handling: 2W or 5W.
X- connector type: SMA, N type or SMB connector.
XX- attenuation: **dB.
XX- frequency range, 06: DC to 6GHz
 14: DC to 14GHz
 18: DC to 18GHz.


FREQ. RANGE (GHz)	Typical VSWR(:1)	Maximum VSWR(:1)
DC to 6	1.20	
6 to 12	1.25	
12 to 18	1.35	
DC to 18		1.40

Material & Plating


Parts	Material	Plating(Micro-inch)
Body & Nut	Stainless Steel	Passivated
Contact (female & male)	Beryllium Copper	Gold 30
Insulator	Teflon	

Characteristic

For example the testing curves of FAT1810S2



Package Outlines



Package type: SMA

Note: all dimensions shown in mm

Yantel Corporation

Add : 3F, Building 3, Southern District 2 of Zhongguan Honghualing Industrial Park, Xili, Nanshan, Shenzhen, China

Tel : 86-755-8355-1886 Fax : 86-755-8355-2533

For detailed performance specs & shopping online see Yantel web site : www.yantel-corp.com